





Evaluation ENERBUILD-Tool – Existing Building Polo Scolastico Ovada Lotto I







1 Basic information about the building

	,	
Name of the building	Polo Scolastico Ovada lotto I	
Address of the building	Strada Voltri n. 27	
Owner/investor	Provincia di Alessandria	
Year of construction	2006-2007	
Building type	Massive construction	
Building method	Concrete framework and brick wall	
Number of buildings	1	
Number of levels above earth	3	
Number of levels underground	0	
Kind of the public use	Educational use: high school	
Effective area for public use in m 2 (net)	1960,00	
Additional private uses	0,00	
Effective area for private use in m 2 (net)	0,00	
Total effective area in m ²	1960,00	
Source of energy for heating	Methane	
Heating system	Methane boiler	
Water heating system	Solar Panels	
Date of the building evaluation	20 July 2011	







2 Execution of the building evaluation with the ENERBBUILD tool

Responsible Organisation: Environment Park S.p.A.

Contact person: Arch. Stefano Dotta / Arch. Chiara Bianco

Telephone: +39 011/2257262 Email: <u>stefano.dotta@envipark.com</u> / <u>chiara.bianco@envipark.com</u>

3 Results

Nr.		Title	Must criteria (M)	max. points	evaluated points	
Α		Quality of location and facilities		max. 100	87,5	
Α		Access to public transport network		50	50	
Α	2	Ecological quality of site		50	37,5	
В		Process and planning quality		max. 200	80	
В	1	Decision making and determination of goals		25	15	
В	2	Formulation of verifiable objectives for energetic and ecological measures	М	20	0	
В	3	Standardized calculation of the economic efficiency	М	40	0	
В	4	Product-management - Use of low-emission products		60	20	
В	5	Planning support for energetic optimization		60	20	
В	6	nformation for users		25	25	
С		Energy & Utilities (Passive house)		max. 350	82	
С	1	Specific heating demand (PHPP)	М	100	0	
С	2	Specific cooling demand (PHPP)	М	100	82	
С	3	Primary energy demand (PHPP)	М	125	0	
С	4	CO2-emissions (PHPP)		50	0	
D		Health and Comfort		max. 250	165	
D	1	Thermal comfort in summer		150	65	
D	2	Ventilation - non energetic aspects		50	50	
D	3	Daylight optimized (+ lightening optimized)		50	50	
Е		Building materials and construction		max. 200	133	
Е	1	OI3 _{TGH-Ic} ecological index of the thermal building envelope (respectively OI3 of the total mass of the building)		200	133	
Su	Sum			max. 1000	547,5	













4 Conclusions from the building evaluation with the ENERBUILD-Tool

a) Generally

ENERBUILD-Tool has been one interesting trans-national system for knowing many energy technicians and experts from other Countries, and also from different Italian Areas, and so for comparing the level of designing and working in Provincia di Alessandria.

b) About the planning process

ENERBUILD Tool use has not been simple for Provincia di Alessandria, because technicians are involved in calculations with PHPP which has not known in our design and working studios. In particular we have noticed strong differences between common Italian evaluations and C2, C3, C4

and E1 values provided by ENERBUILD Tool.

c) About the building itself

Provincia di Alessandria has been involved in ENERBUILD-Tool / WP6 for 7 samples, 3 of which are about new pubblic buildings. For these 3 buildings the planning process required by ENERBUILD Tool is similar to that one used in common administration process in Italy.

d) About the evaluation process

ENERBUILD Tool can't be generally used in our regions, with particular references to materials and ecological index catalogue by IBO BOOK which provides only for Austrian or German areas.

In particular LCA – Life Circle Assessment-, about which OI3 is evaluated, is only based over Austrian data basis.

5 Suggestions for improvement of the ENERBUILD-Tool

ENERBUILD Tool could be an additional tool, not unique, in evaluating public building – offices, schools, gymnasiums – towards local tools.

ENERBUILD Tool / Version 1.7 – 25 November 2010 – has already been studied for transnational uses, in each case with all limits before explained.





